

Time Code Driven Clock



The **TCDS16** Digital Clock syncs to IRIG-B, SMPTE and EBU time codes for accurate and traceable time. The unit configures to time zone and Daylight Saving Time parameters. WinDiscovery software is included.







LED available in red, green, blue or amber

TIME CODE

UBAL BAL

pictured: TCDS16 Desktop Version

Standard Features

- 1 in (2.5 cm) 6-digit LED display
- LED available in red, green, blue or amber
- Synchronizes to IRIG-B, SMPTE 12M, 309M, 24/25/30 fps, 29.97 drop frame
- Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- Configures to time zone and Daylight Saving Time
- WinDiscovery software utility included for easy configuration through USB
- Configuration is saved to non-volatile memory and survives power losses
- · Password protection prevents unauthorized tampering
- Display time in 12- or 24-hr format hh:mm:ss
- Display time & date or UTC & local time
- Display date mm:dd:yy, dd:mm:yy or yy:mm:dd
- · PM indicator
- Auto alternate display between date and time
- · Adjustable brightness levels with scheduled dimming
- Visibility: 50 feet (15 meters)



Options

TCDS16-RM

- Rack mount version (TCDS16-RM pictured above)
- Surface mount (desktop version, pictured top)
- Tilt-wall bracket

Pair with the RC1000 or RC600 to add count-up and count-down timer control functionality





Specifications

CONNECTORS

- BNC female (UBAL)
- 3-pin terminal block (BAL)
- USB for configuration
- 2.1 mm female DC power plug
- IEC C5 A/C Power

POWER

- Choice of IEC AC or DC (24 VDC)
- International IEC AC 90-240v, 50/60 Hz
- Power consumption < 6W

OPERATING PARAMETERS

- Temperature: 0° to 60°C
- Humidity: Up to 90% (non-condensing)
- Storage Temperature: -40° to 185° F (-40° to 85°C)
- Storage Humidity: Up to 90% (non-condensing @ 25°C)

PHYSICAL

- Black Metal Chassis
- IP Rating: IP40
- Surface mount (desktop version)
- Size: 10.7w x 1.7h x 3.5d in (27.2w x 4.31h x 8.9d cm)
- Weight: 1.0 lbs (0.45 kg)
- Size with rack-mount: 16.9w x 1.7h x 3.5d in (43w x 4.31h x 8.9d cm)
- Weight: 1.73 lb (0.78 kg)

MTBF

86,700 - 100,000 hrs
All calculated using Fixed/Ground Mil HDBK 217F assumption

COMPLIANCE

• FCC, ROHS, CE Marked, ANSI

5-YEAR LIMITED PARTS & LABOR WARRANTY MADE IN THE USA